

WHAT IS CLAIMED IS:

SUBV

1. A rotary cutting head for cutting rock by crushing, comprising:

a support;

a cone cutter rotatably mounted by bearings on the support;

rows of welded-on crushing elements adhered to a base body of the  
cone cutter by a metallurgical bond, each crushing element comprising  
a body having a working portion, an opposing mounting portion, and an  
intermediate portion from which the working and mounting portions  
extend, each crushing element having a greatest width D at the  
intermediate portion, and a greatest height H extending from a tip of  
the working portion to a transition between the intermediate portion  
and the mounting portion, wherein  $H/D < 1.2$ .

2. The cutting head according to claim 1 wherein the cutting head  
comprises a drill bit having a plurality of the supports, the supports comprising  
legs.

3. A crushing element adapted for use on a rotary cone cutter, the  
crushing element comprising a cemented carbide body having a top working  
portion, an opposing bottom mounting portion of generally conical shape, and  
an intermediate portion from which the mounting portion extends, the  
crushing element having a greatest width D at the intermediate portion,

SUBA17

and a greatest height H extending from a tip of the mounting portion to a transition between the intermediate portion and the mounting portion, wherein  $H/D < 1.2$ .

5 4. The crushing element according to claim 3 wherein the mounting portion includes a spigot extending downwardly from a center of a bottom of a conical section of the mounting portion, the spigot extending symmetrically about a central axis of the crushing element.

5. The crushing element according to claim 3 wherein the mounting portion forms an internal cone angle from  $150^\circ$  to less than  $180^\circ$ .

10 6. The crushing element according to claim 3 wherein the intermediate portion has a height no greater than 15 mm.

15 7. A rotary cone cutter adapted to be rotatably mounted on a rotary cutting head, the cone cutter comprising a base body, and rows of welded-on crushing elements adhered to the base body by metallurgical bonds, each crushing element comprising a body having a working portion, an opposing mounting portion, and an intermediate portion from which the working mounting portions extend, each crushing element having a greatest width D at the intermediate portion, and a greatest height H extending from a tip of the working portion to a transition between the intermediate portion and the mounting portion, wherein  $H/D < 1.2$ .

20 8. A method of manufacturing a rotary rock-crushing cone cutter comprising the steps of:

- 5 A) providing a base body, and a plurality of crushing elements, each crushing element comprising a body having a working portion, an opposing mounting portion, and an intermediate portion from which the working and mounting portions extend, each crushing element having a greatest width D at the intermediate portion, and a greatest height H extending from a tip of the working portion to a transition between the intermediate portion and the mounting portion, wherein  $H/D < 1.2$ ;
- 10 B) connecting the base body to one pole of an electric circuit, and connecting one of the crushing elements to another pole of the circuit;
- C) bringing a surface of the mounting portion of the crushing element toward a supporting surface of the base body and energizing the circuit to create an electric arc between the mounting portion and the supporting surface;
- 15 D) maintaining the arc sufficiently to melt both the surface of the mounting portion and the supporting surface;
- E) pressing the melted surfaces together;
- F) permitting the pressed-together melted surfaces to solidify; and
- G) repeating steps B-F for the remaining crushing elements.

9. The method according to claim 8 wherein the electric circuit is energized by a capacitor pack in step C, the mounting portion including a spigot projecting downwardly from a center of a bottom of a conical segment of the mounting portion, step C comprising bringing the spigot into contact  
5 with the supporting surface to short-circuit the capacitor pack.

10. The method according to claim 8 wherein step C comprises contacting the mounting portion with the supporting surface and then energizing the circuit while simultaneously lifting the mounting portion off the supporting surface to form the electric arc.

add A27

add B27